

PATENTS
112008-0027C1

IN THE CLAIMS:

Kindly add new claim 42, which is included in the set of pending claims below.

- 6112
- 1 1. (Currently amended) A system for measuring tape pack radii, comprising:
 - 2 a tape supply reel, said tape supply reel rotating as a tape leaves said tape supply
 - 3 reel during a tape transfer process;
 - 4 a tape take-up reel for receiving tape from said tape supply reel, said tape take-up
 - 5 reel rotating to receive said tape during said tape transfer process;
 - 6 a first angular position transducer to measure ~~an~~ a first angular position of said
 - 7 tape supply reel;
 - 8 a second angular position transducer to measure ~~an~~ a second angular position of
 - 9 said tape take-up reel;
 - 10 a third angular position transducer to measure ~~an~~ a third angular position of a me-
 - 11 chanical device used to facilitate said tape transfer process, said mechanical device
 - 12 changing said third angular position as in response to said tape leaves leaving said tape
 - 13 supply reel and is being received by said tape take-up reel;
 - 14 a processor having a Kalman filter, said Kalman filter responsive to one or both of
 - 15 ~~an said first and second angular position measurements by said first angular position~~
 - 16 ~~transducer and an angular position measurement by said second angular position trans-~~
 - 17 ~~ducer and also responsive to an said third angular position measurement by said third an-~~
 - 18 ~~gular position transducer, said Kalman filter including a mathematical model for to cal-~~
 - 19 ~~culating an updated estimate of one or both of a supply radius of a tape pack on said tape~~
 - 20 ~~supply reel and a take-up radius of a tape pack on said tape take-up reel;~~
 - 21 a servo-controller, responsive to ~~one or both of said~~ estimate of one or both of
 - 22 said supply radius and said take-up radius, to control rotation of said tape supply reel and
 - 23 said tape take-up reel.

PATENTS
112008-0027C1

912
1 2. (Currently amended) The ~~apparatus-system~~ as in claim 1, wherein said Kalman
2 filter further comprises:

3 a supply Kalman filter responsive to said first angular position ~~transducer-meas-~~
4 ~~urement~~ and said third angular position ~~transducer-measurement~~;

5 a take-up Kalman filter responsive to said second angular position ~~transducer~~
6 ~~measurement~~ and said third angular position ~~transducer-measurement~~.

1 4. (Currently amended) The ~~apparatus-system~~ as in claim 1, ~~further comprising:~~
2 ~~wherein said mechanical device is a capstan, said tape contacting said capstan and said~~
3 ~~capstan rotating as said tape transfers from said tape supply reel to said tape take-up reel.~~

1 5. (Currently amended) The ~~apparatus-system~~ as in claim 1, wherein said third an-
2 gular position transducer further comprises:

3 an encoder responsive to an angular position of a capstan.

1 6. (Currently amended) The ~~apparatus-system~~ as in claim 1 further comprising:
2 a tape length estimator responsive to said Kalman filter to determine the amount
3 of tape available for a record operation.

1 7. (Currently amended) A system for measuring a length of tape available for a rec-
2 ord operation, comprising:

3 a tape supply reel, said tape supply reel rotating as a tape leaves said tape supply
4 reel during a tape transfer process;

5 a tape take-up reel for receiving tape from said tape supply reel, said tape take-up
6 reel rotating to receive said tape during said tape transfer process;

7 a first ~~angular position~~ transducer to measure ~~on a first~~ angular position of said
8 tape supply reel;

9 a second ~~angular position~~ transducer to measure ~~on a second~~ angular position of
10 said tape take-up reel;

PATENTS
112008-0027C1

CR

11 a third angular position transducer responsive to movement of said tape as said
 12 tape is transferred from said supply reel to said take-up reel;
 13 a processor having a Kalman filter, said Kalman filter responsive to one or both of
 14 an said first and second angular position measurements by said first angular position
 15 transducer and an angular position measurement by said second angular position trans-
 16 ducer and also responsive to an a third angular position measurement by said third angu-
 17 lar position transducer, said Kalman filter including a mathematical model for to deter-
 18 mining an updated estimate of one or both of a supply radius of a tape pack on said tape
 19 supply reel and a take-up radius of a tape pack on said tape take-up reel for calculating
 20 said available length of tape; and
 21 a servo-controller, responsive to said estimate of one or both of said supply radius
 22 and said take-up radius, to control rotation of said tape supply reel and said tape take-up
 23 reel.

1 8. (Currently amended) A method for estimating a radius of a tape on a supply reel
 2 and on a take-up reel, comprising:
 3 measuring a first angular position of a said tape supply reel;
 4 measuring a second angular position of a said tape take-up reel;
 5 measuring a third angular position of a capstan that rotates to transfer the tape
 6 between said tape supply and take-up reels; and,
 7 estimating, by a processor employing that employs a Kalman filter including a
 8 mathematical model, a radius of a tape pack on said supply reel and a radius of a tape
 9 pack on said take-up reel, in response to said first angular position of said tape supply
 10 reel, said second angular position of said tape take-up reel, and said third angular position
 11 of said capstan.

1 9. (Currently amended) The method as in claim 8 wherein said estimating step by
 2 said processor having employing a Kalman filter further comprises:
 3 responding to obtaining an initial estimate of said radius of a tape pack on said
 4 supply reel;

PATENTS
112008-0027C1

612

5 ~~responding to obtaining~~ an initial estimate of a radius of a tape pack on said take-
6 up reel; and,
7 ~~responding to said first angular position measurement, said second angular posi-~~
8 ~~tion measurement, and said third angular position measurement to compute~~ computing
9 said radius of said tape pack on said supply reel and said radius of said tape pack on said
10 take-up reel based on said initial estimate of said radius of a tape pack on said supply
11 reel, said initial estimate of a radius of a tape pack on said take-up reel, said first angular
12 position, said second angular position and said third angular position.

1 10. (Currently amended) The method of claim 8 further comprising:
2 ~~making-measuring~~ said first angular ~~measurement position~~ at a first regular time
3 interval;
4 ~~making-measuring~~ said second angular ~~measurement position~~ at a second regular
5 time interval; and,
6 ~~making-measuring~~ said third angular ~~measurement position~~ at a third regular time
7 interval.

1 11. (Original) The method of claim 10 further comprising:
2 choosing said first regular time interval, said second regular time interval and said
3 third regular time interval each to be approximately 20 milliseconds.

1 12. (Currently amended) A method for estimating a length of a tape on ~~at least one~~
2 tape supply reel and on a tape take-up reel, the method comprising:
3 measuring a first angular position of a said tape supply reel ~~of said at least one~~
4 reel;
5 measuring a second angular position of a said tape take-up reel ~~of said at least one~~
6 reel;
7 measuring a third angular position in response to movement of said tape; and,
8 estimating, by a processor ~~employing that employs~~ a Kalman filter including a
9 mathematical model, said length of tape on ~~said at least one reel~~ tape supply and tape

PATENTS
112008-0027C1

612

10 take-up reels, in response to said first angular position of said tape supply reel, said sec-
11 ond angular position of said tape take-up reel, and said third angular position measured in
12 response to movement of said tape.

1 13. (Currently amended) The ~~apparatus system as in claim 1, wherein: said first, sec-~~
2 ~~ond, and third angular position transducers further comprise:~~
3 said first angular position transducer comprises a first, second, and third optical
4 encoder responsive to the said first angular position of the tape supply reel;
5 said second angular position transducer comprises a second optical encoder re-
6 sponsive to said second angular position of the tape take-up reel; and
7 the said third angular position transducer, respectively comprises a third optical
8 encoder responsive to said third angular position of the mechanical device.

1 14. (Currently amended) A method for estimating a length of tape ~~on a transferred~~
2 from a tape supply reel to a tape take-up reel, comprising:
3 measuring a first angular position of a said tape supply reel;
4 measuring a second angular position of a said tape take-up reel;
5 measuring a third angular position of a capstan engaging the tape as said tape is
6 transferred from said tape supply reel to said tape take-up reel; and,
7 estimating said length of tape by a processor employing a Kalman filter including
8 a mathematical model, said Kalman filter responsive to at least one of said first and sec-
9 ond angular positions of said tape supply reel, said second angular position of said tape
10 take-up reel, and also responsive to said third angular position of said capstan.

1 15. (Currently amended) A method for estimating a length of a tape ~~on one or more a~~
2 tape reels, comprising:
3 selecting said tape reel from one or more tape reels;
4 measuring a first angular position of a tape supply reel of said one or more
5 reels said tape reel;

PATENTS
112008-0027C1

6 ~~measuring a second angular position of a tape take-up reel of said one or more~~
7 ~~reels;~~
8 ~~measuring a third-second angular position of a capstan engaging the said tape;~~
9 ~~measuring a fourth-third angular position of a tape tension arm; and~~
10 ~~selecting either said tape supply reel or said take-up reel as a selected reel; and~~
11 ~~estimating said length of said tape by a processor employing a Kalman filter in-~~
12 ~~cluding a mathematical model, said Kalman filter responsive to said measured first, sec-~~
13 ~~ond and third angular positions of said selected reel, said third angular position of said~~
14 ~~capstan, and said fourth angular position of said tape tension arm.~~

1 16. (Currently amended) The method of claim 14 comprising:

2 measuring a fourth angular position of a tape engaging member which causes a
3 change in the ~~a~~ tape path length as tape is unwound from and wound onto the supply and
4 take-up reels, respectively; and,

5 the step of estimating by a processor employing a Kalman filter includes said
6 Kalman filter being responsive to said fourth angular position of said tape engaging
7 member as well as the measured first, second, and third angular positions.

1 17. (Currently amended) A method for estimating the amount of tape on a tape reel,
2 comprising:

3 measuring a first angular position of said tape reel;

4 measuring a second angular position of a cylindrical member engaging and rotat-
5 ing with the tape as the tape moves along a tape path;

6 measuring a third angular position of a tension arm engaging the tape between
7 said reel and said cylindrical member; and,

8 estimating how much tape is on said tape reel by a processor employing a Kalman
9 filter including a mathematical model, said Kalman filter responsive to said first angular
10 position of said tape reel, said second angular position of said cylindrical member, and
11 said third angular position of said tension arm.

PATENTS
112008-0027C1

GR

1 18. (Previously added) The method of claim 17 wherein the cylindrical member en-
2 gages the tape to cause the tape to follow the tape path.

1 19. (Previously added) The method of claim 17 wherein the cylindrical member is a
2 capstan that engages the tape and upon rotation causes the tape to move along the tape
3 path.

1 20. (Currently amended) A system for measuring how much tape is on a reel from
2 and to which tape is unwound and wound respectively during the rotation of the reel as
3 the tape is moved along a tape path, comprising:

4 a cylindrical member engaging the tape at a position along the tape path that es-
5 tablishes a tape path length from the reel, said cylindrical member engaging said tape,
6 said cylindrical member rotating as the tape is moved along the tape path;

7 a first angular position transducer for measuring a first angular position of said
8 reel as the tape is moved along the tape path;

9 a second angular position transducer for measuring a second angular position of
10 the cylindrical member as the tape is moved along the tape path; and

11 a processor including a Kalman filter responsive to the first and second angular
12 positions measured by the first and second angular position transducers, said Kalman fil-
13 ter including a mathematical model for calculating how much tape is on said reel.

1 21. (Previously added) The system as in claim 20 wherein the tape cylindrical mem-
2 ber engages the tape to cause this tape to follow the tape path.

1 22. (Previously added) The system as in claim 20 wherein the tape cylindrical mem-
2 ber is a capstan that engages the tape and upon rotation causes this tape to move along the
3 tape path.

PATENTS
112008-0027C1

23. (Previously added) The system as in claim 20 further comprising:
a second member engaging the tape which causes a change in the tape path length from the reel to the position at which the cylindrical member engages the tape as the tape is moved along the tape path;
a third angular position transducer for measuring a third angular position of the second member as the tape is moved along the tape path; and
said processor calculating how much tape is on the reel in response to the third angular position measured by the third angular position transducer as well as the measured first and second angular positions.
24. (Previously added) The system of claim 23 wherein the second tape engaging member is a tension arm mechanism that engages tape at a position along the tape path between the reel and the cylindrical member.
25. (Currently amended) A method for measuring how much tape is on a reel from and to which tape is unwound and wound respectively during the rotation of the reel as the tape is moved along a tape path, comprising:
measuring the amount of rotation by the reel as the tape is unwound from and/or wound onto the reel;
measuring the amount of movement of the tape along the tape path as the tape is unwound from and/or wound onto the reel, the movement of the tape measured at a position along the tape path that establishes a tape path length from the reel; and,
calculating, by a processor that employs a Kalman filter including a mathematical model, how much tape is on the reel in response to the measured amount of rotation by the reel and the measured amount of movement of the tape.
26. (Currently amended) The method of claim 25 further comprising:
measuring the amount of change in the tape path length as the tape is unwound from and/or wound onto the reel; and,

G12

PATENTS
112008-0027C1

4 said step of calculating how much tape is on the reel is in response to the meas-
5 ured amount of change in the tape path length as well as the measured amounts of reel
6 rotation and tape movement.

1 27. (Currently amended) The method of claim 25, further comprising:

2 a. ~~choosing a variable to be measured; combining said measured amount of rota-~~
3 ~~tion by said reel and said measured amount of movement of the tape along the tape path~~
4 ~~to derive a measured radius of tape on said reel;~~

5 b. selecting a minimum and maximum acceptable measurement value of said
6 ~~variable measured radius;~~

7 c. ~~if said measured radius is less than the minimum acceptable value of said ra-~~
8 ~~dus, then setting the value of the measured radius to the minimum acceptable measu-~~
9 ~~rement value of said radius;~~

10 d. ~~if said measured radius is greater than the maximum acceptable value of said~~
11 ~~radius, then setting the value of the measured radius to the maximum acceptable meas-~~
12 ~~urement value of said radius;~~

13 e.g. selecting a maximum acceptable variance ~~of corresponding to said variable-~~
14 ~~measured radius;~~

15 d.f. ~~recording an individual measurement; calculating a measured variance based on~~
16 ~~said measured radius;~~

17 e.g. determining if said ~~individual measurement's~~ measured variance is greater than
18 said maximum acceptable variance;

19 f.h. determining if a three sigma-interval around said ~~individual measurement-~~
20 ~~measured radius~~ is not at least partially included within an interval from said minimum to
21 said maximum acceptable radius measurement values; and

22 g.i. if the determinations in steps e.g OR f.h prove true, ignoring the individual
23 ~~measurement measured radius~~ and ~~basing calculating an estimate of how much tape is on~~
24 ~~the reel based on one or more previous estimates of how much tape is on the reel~~ the cur-
25 rent Kalman filter estimate on other measurements and on previous Kalman filter esti-
26 mates.

PATENTS
112008-0027C1

312

1 32. (Currently amended) The ~~apparatus system~~ as in claim 1 wherein said third an-
2 gular position transducer further comprises:
3 an encoder responsive to an angular position of a supply reel tension arm.

1 33. (Currently amended) The ~~apparatus system~~ as in claim 1 wherein said third an-
2 gular position transducer further comprises:
3 an encoder responsive to an angular position of a take-up reel tension arm.

1 34. (Currently amended) A method for estimating a length of a tape on a reel, com-
2 prising:
3 a. ~~choosing a variable to be measured, said variable related to estimating a~~
4 ~~length of tape on a reel; obtaining a measured radius of tape on said reel;~~
5 b. selecting a minimum and maximum acceptable measurement value of said
6 ~~variable~~ measured radius;
7 c. ~~if said measured radius is less than the minimum acceptable value of said~~
8 ~~radius, then setting the value of the measured radius to the minimum acceptable meas-~~
9 ~~urement value of said radius;~~
10 d. ~~if said measured radius is greater than the maximum acceptable value of~~
11 ~~said radius, then setting the value of the measured radius to the maximum acceptable~~
12 ~~measurement value of said radius;~~
13 e.g. selecting a maximum acceptable variance of ~~corresponding to said vari-~~
14 ~~able~~ measured radius;
15 d.f. ~~calculating a measured variance based on said measured radius; recording~~
16 ~~an individual measurement of said variable;~~
17 e.g. determining if said ~~individual measurement's~~ measured variance is greater
18 than said maximum acceptable variance;
19 f.h. determining if a three sigma-interval around said ~~individual measure-~~
20 ~~ment~~ measured radius is not at least partially included within an interval from said mini-
21 mum to said maximum acceptable radius measurement values; and

PATENTS
112008-0027C1

22 i. ~~if the determinations in steps e-g OR f-h prove true, ignoring the individual~~
 23 ~~measurement measured radius and estimating said length of said tape on said reel based~~
 24 ~~on one or more previous estimates of said length of said tape on said reel basing the cur-~~
 25 ~~rent Kalman filter estimate on other measurements and on previous Kalman filter esti-~~
 26 ~~mates.~~

1 35. (Currently amended) A method for estimating a length of tape on a reel, com-
 2 prising:

3 a. ~~choosing a variable to be measured, said variable related to estimating a~~
 4 ~~said length of tape on a said reel;~~

5 b. ~~selecting a minimum and maximum acceptable measurement value of said~~
 6 ~~variable;~~

7 eb. ~~selecting a maximum acceptable variance of corresponding to said vari-~~
 8 ~~able;~~

9 dc. ~~recording obtaining an individual measurement of said variable;~~

10 ed. ~~determining if said individual measurement's variance is greater than said~~
 11 ~~maximum acceptable variance; and~~

12 e. ~~if the determination in step e-d proves true, ignoring the individual meas-~~
 13 ~~urement and basing the a current Kalman filter estimate of said length of tape on said reel~~
 14 ~~on other measurements and on previous Kalman filter estimates.~~

1 36. (Currently amended) A method for estimating a length of tape on a reel, com-
 2 prising:

3 a. ~~choosing a variable to be measured, said variable related to estimating a~~
 4 ~~said length of tape on a said reel;~~

5 b. ~~selecting a minimum and maximum acceptable measurement value of said~~
 6 ~~variable;~~

7 e. ~~selecting a maximum acceptable variance of said variable;~~

8 dc. ~~recording obtaining an individual measurement of said variable;~~

PATENTS
112008-0027C1

G12

9 ed. determining if a three sigma-interval around said individual measurement
10 is not at least partially included within an interval from said minimum to said maximum,
11 acceptable radius measurement values; and,
12 e. if the determination in step e-d proves true, ignoring the individual meas-
13 urement and basing the a current Kalman filter estimate of said length of tape on said reel
14 on other measurements and on previous Kalman filter estimates.

1 37. (Currently amended) The method of ~~claim 34 or claim 35~~ or claim 36 further
2 comprising:
3 choosing as said variable an angular position of said reels measured radius, said
4 measured radius being derived at least based on a measured angular position of a supply
5 tape reel.

1 38. (Currently amended) The method of ~~claim 34 or claim 35~~ or claim 36 further
2 comprising:
3 choosing as said variable an angular position of a second reel upon which said
4 tape is wound a measured radius, said measured radius being derived at least based on a
5 measured angular position of a take-up tape reel.

1 39. (Currently amended) The method of ~~claim 34 or claim 35~~ or claim 36 further
2 comprising:
3 choosing as said variable an angular position of a transducer, said transducer re-
4 sponsive to movement of said tape a measured radius, said measured radius being derived
5 at least based on a measured amount of said tape which is transferred between a supply
6 tape reel and a take-up tape reel.

1 40. (Currently amended) The method of claim 39, ~~further comprising wherein said~~
2 measured amount of said tape which is transferred between said supply tape reel and said
3 take-up tape reel is measured based on a

PATENTS
112008-0027C1

4 ~~choosing said transducer to measure~~ angular position of a capstan, said tape in contact
5 with said capstan, said capstan rotating as said tape moves.

1 41. (Currently amended) The method of claim 39, ~~further comprising wherein said~~
2 measured amount of said tape which is transferred between said supply tape reel and said
3 take-up tape reel is measured based on a
4 ~~choosing said transducer to measure~~ an angular position of a tension arm in contact
5 with said tape.

1 42. (New) A method for estimating a length of a tape on a tape reel, comprising:
2 measuring an angular position of said tape reel;
3 measuring a length of said tape which is unwound from or wound onto said tape
4 reel during a regular time interval; and,
5 estimating, by a processor that employs a Kalman filter including a mathematical
6 model, said length of said tape on said tape reel in response to said measured angular po-
7 sition of said tape reel and said measured length of said tape which is unwound from or
8 wound onto said tape reel during a regular time interval.